

OBMW2.E63382 - MAGNET WIRE - COMPONENT

Magnet Wire - Component

See General Information for Magnet Wire - Component

ELEKTRISOLA INC

E63382

126 High St

Boscawen, NH 03303-2808 USA

Material Designation	Mark Dsg	Base Coat	Top Coat	ANSI Type	Temp Class
Amidester 200	A200	Polyester-imide	-	MW 74-C	200
Amidester AI210	AI210	Polyester-imide	Polyamide-imide	MW 35-C	200
		Polyester-imide	Polyamide-imide	MW 73-C	200
Amidimide 220	I220 or G220	Polyamideimide	-	MW 81-C	220
EN180	EN180	Polyester	Polyamide	MW 78-C	180
Estersol 155	PEW-S	Polyester	-	MW 26-C	155[#]
Estersol 180	E180 or GE180	Solderable Polyester-imide	-	MW 77-C	180
Polyimide 240	ML 240	Aromatic Polyimide	-	MW 16-C	240
Polysol 155	P155, G155	Polyurethane	-	MW 79-C	155
		Polyurethane	-	MW 75-C	130[#]
Polysol 155g	Pg155	Polyurethane	-	MW 75-C	130[#]
Polysol 155p	Pp155, Gp155	Polyurethane	-	MW 79-C	155[#]
Polysol 160	P160	Polyurethane	-	MW 79-C	155
Polysol 170	P170, G170	Polyurethane	-	MW 79-C	155
Polysol 180	P180, G180, Pv180	Polyurethane	-	MW 82-C	180
		Polyurethane	-	MW 79-C	155[#]
Polysol 180 FIW	P180 FIW	Polyurethane	-	MW 85-C	180
Polysol 210	Polysol 210	Polyurethane	-	MW 82-C	180
Polysol N155	PN155	Polyurethane	Polyamide	MW 80-C	155
		Polyurethane	Polyamide	MW 28-C	130[#]
Polysol N155p	PN15p	Modified Polyurethane	Polyamide	MW 80-C	155

Polysol N180	PN180	Polyurethane	Polyamide	MW 83-C	180
Polysol P155p	P155p, G155p	Polyurethane	-	MW 79-C	155
Polysol P210	Polysol P210	Polyurethane	-	MW 82-C	180
Posyn 155	Posyn 155	Polyurethane	-	MW 79-C	155

Material Designation	Mark Dsg	Base Coat	Top Coat	Bond Coat	ANSI/Conductor Type	Temp Class
LITZWIRE (a)(b)(c)(d)(e)	LITZWIRE (a)(b)(c)(d)(e)	-	-	-	-	-
Solabond (Z)SP18, Thermobond STP18	Solabond (Z)SP18, Thermobond STP18	Polyurethane	-	Polyamide (self-bonding)	MW 131-C	155
Solabond LYP18	LYP18	Polyurethane	Polyamide	-	-	180
Thermobond RT21	RT21	Polyester	Polyamide-imide	Polyamide (self-bonding)	MW 102-C	180[#]

[#] - The magnet wire may perform better than the rating reflects and may not be suitable for insulation system, varnish or end-product testing. Further consideration is necessary prior to its use in testing.

(a) - Number of wire strands x Diameter of each wire strand.

(b) - One of the following mark designations, showing the type of magnet wire: E180-MW77, A200-MW74, PN155-MW80, P155-MW79, G155-MW75, P180-MW82, G180-MW82, PN180-MW83, P170-MW79, G170-MW79, PV180-MW82, P155p-MW79. AI210-MW35, MW73, Posyn 155-MW79, (Z)SP18, STP18, LYP18, RT18, RTP18, XTP18.

(c) - Optional suffix 0, 1, 2, 3, single, heavy or triple specifying single, heavy or triple build.

(d) - 1 for single serving, 2 for double serving.

(e) - Two digit number, 52, 60 or 63.

(Z) - Maybe replaced with any letter "A"- "W", inclusive, to denote difference in lubricant.

Marking: Company name or trademark **ELEKTRISOLA** and material designation or marked designation on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2018-12-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"